

# KULOVÉ KOHOUTY PN 50-100

## BALL VALVES PN 50-100

### KÓDOVACÍ KLÍČ:

### CODE KEY:

<b>15 44</b>	<b>DN15</b>	<b>RB</b>	<b>BW/BW</b>	<b>TRCC</b>	<b>1 0 0</b>
<b>① ②</b>	<b>③</b>	<b>④</b>	<b>⑤</b>	<b>⑥</b>	<b>⑦ ⑧ ⑨</b>

- |  |   |
|--|---|
| <p><b>①</b> Sériové číslo<br/>typ 15i, 17i, 26</p> <p><b>②</b> Materiál kulového kohoutu<br/>44 - uhlíková ocel<br/>66 - nerez ocel</p> <p><b>③</b> Jmenovitý rozměr<br/>DN 8-150</p> <p><b>④</b> Průtok<br/>RB - redukovaný průtok DN 15-150<br/>FB - plný průtok DN 8-100</p> <p><b>⑤</b> Typ připojení<br/>BW/BW - přivařovací<br/>SW/SW - násuvné, přivařovací<br/>BSP/BSP - trubkový závit<br/>NPT/NPT - metrický závit</p> <p><b>⑥</b> Materiál sedel a těsnících kroužků<br/>TRCC<br/>T ..... sedlo<br/>R ..... těsnění tělesa<br/>C ..... těsnění vřetene<br/>C ..... těsnění vřetene<br/>druhy viz dále</p> <p><b>⑦</b> Typ páky<br/>0 - standardní páka<br/>1 - bez páky<br/>2 - lomená páka<br/>3 - ochranná páka<br/>4 - uzamykatelné provedení<br/>5 - T - páka</p> <p><b>⑧</b> Provedení koule<br/>0 - standard<br/>1 - tlakově odlehčená<br/>2 - antistatická<br/>3 - Monelův kov</p> <p><b>⑨</b> Provedení pláště<br/>0 - standard<br/>1 - vyhřívaný plášť</p> | <p><b>①</b> Serie number<br/>type 15i, 17i, 26</p> <p><b>②</b> Ball valve material<br/>44 - carbon steel<br/>66 - stainless steel</p> <p><b>③</b> Size<br/>from DN 8 up to DN 150</p> <p><b>④</b> Bore<br/>RB - reduced bore DN 15-150<br/>FB - full bore DN 8-100</p> <p><b>⑤</b> Ends<br/>BW/BW - butt weld end<br/>SW/SW - socket weld end<br/>BSP/BSP - screwed end<br/>NPT/NPT - screwed end</p> <p><b>⑥</b> Seals<br/>TRCC<br/>T ..... seat<br/>R ..... body seal<br/>C ..... stem seal<br/>C ..... stem seal</p> <p><b>⑦</b> Handle<br/>0 - standard handle<br/>1 - without handle<br/>2 - cranked handle<br/>3 - safety handle<br/>4 - locking device<br/>5 - T - handle</p> <p><b>⑧</b> Type of ball<br/>0 - standard<br/>1 - pressure relief hole<br/>2 - antistatic<br/>3 - Monel ball and stem</p> <p><b>⑨</b> Type of jacket<br/>0 - standard<br/>1 - heating jacket</p> |
|--|---|