



ČSN 132230

# Svařované tvarovky T

## DN 100 až DN 1800; PN 6 až PN 100

### PN 40

DN	DN1	D	t	D1	t1	d	d1	b	t2	k	F	H	m
100	100	114,3	4	114,3	4,0	106,3	106,3	25	5,6	2	105	-	3,9
	80			88,9	3,6		81,7		4,0			98	3,0
	65			76,1	3,2		69,7		4,0			95	2,8
	50			60,3	2,9		54,5		4,0			89	2,7
125	125	139,7	4,5	139,7	4,5	130,7	130,7	25	7,0	2	124	-	6,2
	100			114,3	4,0		106,3		5,0			117	4,9
	80			88,9	3,6		81,7		4,5			111	4,5
	65			76,1	3,2		69,7		4,5			108	4,3
150	150	168,3	5	168,3	5,0	158,3	158,3	35	9,0	2	143	-	10,1
	125			139,7	4,5		130,7		7,0			137	8,1
	100			114,3	4,0		106,3		5,6			130	7,2
	80			88,9	3,6		81,7		4,5			124	6,6
200	200	219,1	6,3	219,1	6,3	206,5	206,5	40	11,0	2	178	-	20,3
	150			168,3	5,0		158,3		9,0			168	15,9
	125			139,7	4,5		130,7		7,0			162	14,2
	100			114,3	4,0		106,3		6,3			156	13,3
250	250	273	7	273,0	7,0	259,0	259,0	50	16,0	2	216	-	35,9
	200			219,1	6,3		206,5		11,0			203	27,5
	150			168,3	5,0		158,3		9,0			194	24,0
	125			139,7	4,5		130,7		8,0			191	22,6
300	300	323,9	8	323,9	8,0	307,9	307,9	60	18,0	2	254	-	57,4
	250			273,0	7,0		259,0		16,0			241	46,6
	200			219,1	6,3		206,5		12,5			229	40,8
	150			168,3	5,0		158,3		9,0			219	36,2
350	350	355,6	9	355,6	9,0	337,9	337,9	70	20,0	3	279	-	78,5
	300			323,9	8,0		307,9		18,0			270	66,5
	250			273,0	7,0		259,0		16,0			257	58,4
	200			219,1	6,3		206,5		11,0			248	51,8
400	400	406,4	11	406,4	11,0	384,4	384,4	75	20,0	4	305	-	115,0
	350			355,6	9,0		337,6		18,0			305	95,2
	300			323,9	8,0		307,9		16,0			295	87,2
	250			273,0	7,0		259,0		14,0			283	80,3
500	500	508	14	508,0	14,0	480,0	480,0	80	22,0	4	381	-	222,0
	400			406,4	11,0		384,4		18,0			356	167,0
	350			355,6	9,0		337,6		16,0			356	156,0
	300			323,9	8,0		307,9		14,0			346	150,0
400	400	406,4	11	406,4	11,0	384,4	384,4	75	20,0	4	305	-	115,0
350	355,6			9,0	337,6		18,0		305			95,2	
300	323,9			8,0	307,9		16,0		295			87,2	
250	273,0			7,0	259,0		14,0		283			80,3	
500	500	508	14	508,0	14,0	480,0	480,0	80	22,0	4	381	-	222,0
	400			406,4	11,0		384,4		18,0			356	167,0
	350			355,6	9,0		337,6		16,0			356	156,0
	300			323,9	8,0		307,9		14,0			346	150,0
500	500	508	14	508,0	14,0	480,0	480,0	80	22,0	4	381	-	222,0
400	406,4			11,0	384,4		18,0		356			167,0	
350	355,6			9,0	337,6		16,0		356			156,0	
300	323,9			8,0	307,9		14,0		346			150,0	
500	500	508	14	508,0	14,0	480,0	480,0	80	22,0	4	381	-	222,0
400	406,4			11,0	384,4		18,0		356			167,0	
350	355,6			9,0	337,6		16,0		356			156,0	
300	323,9			8,0	307,9		14,0		346			150,0	

### PN 63

DN	DN1	D	t	D1	t1	d	d1	b	t2	k	F	H	m
100	100	114,3	5	114,3	5,0	104,3	104,3	25	8,0	2	105	-	4,9
	80			88,9	4,0		80,9		6,3			98	3,8
	65			76,1	3,6		68,9		5,6			95	3,5
	50			60,3	3,2		53,9		4,0			89	3,2
125	125	139,7	5,6	139,7	5,6	128,5	128,5	30	10,0	2	124	-	8,1
	100			114,3	5,0		104,3		8,0			117	6,2
	80			88,9	4,0		80,9		6,3			111	5,5
	65			76,1	3,6		68,9		5,6			108	5,2
150	150	168,3	7	168,3	7,0	154,3	154,3	40	11,0	2	143	-	14,1
	125			139,7	5,6		128,5		10,0			137	11,3
	100			114,3	5,0		104,3		8,0			130	10,0
	80			88,9	4,0		80,9		6,3			124	9,1
200	200	219,1	8	219,1	8,0	203,1	203,1	45	16,0	2	178	-	26,8
	150			168,3	7,0		154,3		12,5			168	20,9
	125			139,7	5,6		128,5		10,0			162	18,3
	100			114,3	5,0		104,3		8,0			156	16,9
250	250	273	10	273,0	10,0	253,0	253,0	55	20,0	4	216	-	50,4
	200			219,1	8,0		203,1		16,0			203	38,9
	150			168,3	7,0		154,3		12,5			194	34,2
	125			139,7	5,6		128,5		10,0			191	31,8
300	300	323,9	12,5	323,9	12,5	298,9	298,9	65	22,0	4	254	-	86,2
	250			273,0	10,0		253,0		18,0			241	68,3
	200			219,1	8,0		203,1		14,0			229	60,0
	150			168,3	7,0		154,3		11,0			219	55,0
350	350	355,6	12,5	355,6	12,5	330,6	330,6	75	25,0	5	279	-	107,0
	300			323,9	12,5		298,9		22,0			270	87,8
	250			273,0	10,0		253,0		20,0			257	80,5
	200			219,1	8,0		203,1		16,0			248	72,1
350	350	355,6	12,5	355,6	12,5	330,6	330,6	75	25,0	5	279	-	107,0
300	323,9			12,5	298,9		22,0		270			87,8	
250	273,0			10,0	253,0		20,0		257			80,5	
200	219,1			8,0	203,1		16,0		248			72,1	
350	350	355,6	12,5	355,6	12,5	330,6	330,6	75	25,0	5	279	-	107,0
300	323,9			12,5	298,9		22,0		270			87,8	
250	273,0			10,0	253,0		20,0		257			80,5	
200	219,1			8,0	203,1		16,0		248			72,1	

Norma platná od 1. 1. 1991

Tiskařská 690/6a, 108 00 Praha 10  
 Tel.: +420 272 700 860  
 Fax: +420 272 702 153  
 GSM brána: 602 182 090, 606 600 081  
 E-mail: trival@trival.cz

NON-STOP 24 HOD. INFORMAČNÍ  
 A DODÁVKOVÁ SLUŽBA: 602 217 549  
 602 651 061  
 602 219 979

www.trival.cz